Survey of The East Section Line Of Section 36.
Town 17 N. of Range No. 4 West.
County of Monroe.
Wis.

Remarks.
Survey made May 19 & 20, 1908, for John Gilfilan and others, to determine The location of the NE corner of the SE¼ of the NE¼ of said Sect. 36, and The relative location of a certain stone quarry near the north line of the said SE¼ NE¼. Went to the SE corner of said sect. 36 and made examination of the same. Found one bearing tree standing W. Oak N. 70 E. 82 links. Marks rotted out, but overgrowth of wood shows old boxing. This tree is certified to by Thos. Hobson an old settler, who saw same when letters and figures were plain; set a stake from said tree. then run north on an offset-line, var. 5¼ degrees E. to north-east corner of section. Found stump of SW bearing tree with marks very plain; part of the letter B, and all of the letter T. Also found roots of other bearing-trees where same should stand as per org. notes. Then went to the East Quarter corner of said section 36, and made search for same where settlers said that the old corner stood. Found stake hole showing shape of stake point very plain, and verified same by roots of trees where original bearings stood. Renewed corner and then corrected off-set line north to the NE section corner. Then run west on north line of the SE¼ NE¼ of said section about 36 rods to north side of stone Quarry. Found that said Quarry was as far as worked, south of this line. Also made examination in this survey of a tree said to have used by Lacrosse Co. Surveyor as a witness tree. Said tree shows no signs of having ever been a bearing tree. and is [illegible] far west to agree with government notes in any particular. Said tre[illegible] about 36 rods west of SE Sect. corner.

Work done with Fred Holden Co. Surv. of Monroe Co.

Description of corners used and established in this survey.

	Pine 8 S. 60 W. 68 links.	Stump with marks plain as above.
NE Sec. Cor.	B. Oak, N. 32 W. 32 "	Roots found.
	Pine 15 S. 88 E. 53 "	" "
	" 7 N. 47 E. 56 "	" "

Set stone 13X10X5 at corner, and marked new bearing trees thus *
B Oak 6 due west 58 links & B. Oak S. 22 E. 35 links.

SE Sec. cor. One bearing tree standing as in notes above, W. Oak, N 60 E. 82.

E¼ Found as in remarks above, and set stone 15X11X5. W. Oak 16 N 60 E 404 lks.

Respectfully Submitted C. M. Keach Co. Surv. of Jackson Co.

CSR 1648